




Touchstone™

Choose the level of protection to match your needs

Touchstone™ from Polyco is a knitted glove made with 100% Kevlar® aramid fibre.

Kevlar® has an inherent strength protecting against cuts, slashes and abrasion, and is heat retardant making it very practical in industries where burn protection is required. Offering a high cut resistance to weight ratio, the Touchstone™ is available in three different weights allowing the user to select the level of protection required. Delivering exceptional performance, it is seamless, soft and extremely comfortable, which allows for prolonged use without causing irritation. The close fitting design also makes it extremely dextrous. It is machine washable, can be dry cleaned and is ambidextrous, which all contribute to increased longevity.



Case Quantity
12 pairs per polybag
48 pairs per case

Typically Used For

- Steel Handling
- Cable & Couplings
- Can & Bottle Handling
- Press Works
- Glass Manufacturing
- Glazing

Size	7	8	9	10
Lightweight	7500	7501	7502	7503
Mediumweight	-	7511	7512	7513
Heavyweight	-	7521	7522	7523
Length	23cm	24cm	25cm	26cm

Kevlar® is a DuPont registered trademark



Heavyweight Touchstone Only

Statement of Product Conformity

**BM Polyco Ltd
Crown Road
Enfield
EN1 1TX
Great Britain**

Certified to ISO 9001:2008

declare that the new PPE described hereafter



TOUCHSTONE

100% Kevlar[®] Gloves and Sleeves

are in conformity with the provisions of Council Directive 89/686/EEC and where such is the case, with National Standards transposing harmonised standards EN388:2003, EN407:2004 and EN420:2003.

are identical to the PPE which are the subject of EC certificates of conformity issued by SGS United Kingdom Ltd, 202B Worle Parkway, Weston-super-Mare, BS22 6WA, UK (Approved Body No.0120).

**MECHANICAL HAZARDS
EN388:2003**



**THERMAL HAZARDS
EN407:2004**



Intermediate Design



EN407 Test	All styles except 7553
Burning Behaviour	X
Contact Heat	1
Convective Heat	X
Radiant Heat	X
Small splashes of molten metal	X
Large splashes of molten metal	X

EN388 Performance Levels	Abrasion	Blade Cut	Tear	Puncture
Lightweight	1	2	4	X
Mediumweight	1	3	4	X
Heavyweight	1	4	4	X
Lightweight Grip	1	2	4	X
Mediumweight Grip	1	3	4	X
Heavyweight Grip	2	4	4	X
Mediumweight Fingerless Grip	1	3	4	X
12" Sleeve	1	3	4	X
14" Sleeve	1	3	4	X
18" Sleeve	1	3	4	X
22" Sleeve	1	3	4	X
20" Loose Fit Sleeve	1	3	4	X

User Information

Glove care: To get the best service from your gloves ensure that after use all contaminant is removed.

Storage: store in dry conditions away from direct sunlight and heat.

Do not use in or around chlorine bleach.

You are advised to retain this packaging for reference.

Kevlar® is a DuPont registered trademark

Note: should not be worn where there is a risk of entanglement with moving machinery.

Range Available: sizes and codes

Touchstone

Sizes	7	8	9	10
Lightweight glove	7500	7501	7502	7503
Mediumweight glove	7510	7511	7512	7513
Heavyweight glove	7520	7521	7522	7523

Touchstone Grip

Sizes	7	8	9	10
Mediumweight	7530	7531	7532	7533
Heavyweight	7540	7541	7542	7543
Mediumweight Fingerless	7530-FL	7531-FL	7532-FL	7533-FL

Touchstone Sleeves

12" Sleeve (without thumb slot)	7549
14" Sleeve (with thumb slot)	7550
18" Sleeve (with thumb slot)	7551
22" Sleeve (with thumb slot)	7552
20" Loose Fit Sleeve	7553